


# ATS-22R

Order no.: 0257110

## PRODUCT INFORMATION

**16-channel Digital Voice Transmission System, 863-865 MHz**

- Suitable as a tour guide system, trainer/student system and for any other application in which a certain voice source is to be distributed to one or more receivers
- High resistance to interference due to digital transmisison
- Parallel operation of up to 4 different channels possible without any interference
- Licence-free in the EU

**16-channel miniature receiver,**
with intercom function.

- Intercom function with transmitter ATS-22T via push-button
- Built-in microphone
- Supplied with matching clip-on earphone
- Switches off automatically after not receiving an input signal for 20 minutes (power-saving function)
- LCD for indicating channel, carrier signal, volume and battery status
- Power supply via integrated rech. lithium battery (3.7 V/600 mAh)
- Micro USB charging connection for ATS-12CB or USB charger, available at option
- Dimensions: 40 x 87 x 12 mm

**Licence-free in the EU.**

**Manufacturer information:**
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

**Safety Notes and Warning Messages**
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.
Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

## SPECIFICATIONS

**ATS-22R**

**General information**

| | |
|---|---|
| Description | 16-channel digital miniature receiver |
| Carrier frequency range | 863-865 MHz |
| Channels | 1 |
| Operating time | > 15 h |
| Admiss. ambient temp. | 0-40 °C |

**Specifications receiver**

| | |
|---|---|
| Power supply receiver | integrated rech. lithium batt. (3.7 V/600 mAh) |
| Width receiver | 40 mm |
| Height receiver | 87 mm |
| Depth receiver | 12 mm |
| Weight receiver | 37 g |
| Connections receiver | 3.5 mm jack (earphone), micro USB charging port |

**ATS-22R**

| | |
|---|---|
| EAN code | 4007754246230 |
| Net weight | 0.052 kg |