

ATS-80R

Order no.: 0250001

PRODUCT INFORMATION

42-channel digital PLL voice transmission system, 823-832 MHz and 863-865 MHz

- As a tour guide system also suitable for any other application in which a two-way communication is required, e.g. training sessions, lectures with questions and answers and group tours or factory tours
- High resistance to interference due to digital transmission
- High operating range
- Frequency range optimised for voice transmissions
- Interference-free parallel operation of up to 42 different channels possible

42-channel PLL receiver

- Supplied with matching earphone
- Adjustable headphone output
- Automatic switch-off (power-saving function)
- High-contrast OLED display
- Battery status indication
- Push-to-talk button with 3 operating modes (PTT, PTB, PTM)
- Alarm-off button
- Operating range alert
- Call alert

- Mute function
- Automatic channel lock
- Built-in microphone
- Full duplex communication (release by transmitter)
- Hearing Aid Compatible (HAC)
- Belt clip
- Lanyard
- Power supply via 2 x 1.2 V NiMH rech. battery AA size (not supplied)
- Dimensions: 47 x 109 x 35 mm
- Weight: 53 g

Please consider the regulations and requirements in the country of application.

Please read the notes regarding wireless systems in the section “IMPORTANT INFORMATION”!

Matching chargers ATS-85PS, ATS-850PS or charging case ATS-825C are available at option.

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.
Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

SPECIFICATIONS

ATS-80R

General information

Description	42-channel digital PLL receiver
Carrier frequency range	823-832 MHz, 863-865 MHz
Audio frequency range	300-4,500 Hz

ATS-80R

Channels	1
Operating time	> 30 h
Admiss. ambient temp.	0-40 °C

Specifications receiver

Power supply receiver	2 x 1.2 V NiMH rech. batt. AA size
Width receiver	47 mm
Height receiver	109 mm
Depth receiver	35 mm
Weight receiver	53 g
Connections receiver	3.5 mm jack (earphones)

ATS-80R

EAN code	4007754273809
Net weight	0.079 kg