

CDX1-1070/8

Order no.: 1001098

PRODUCT INFORMATION

PA horn driver, 24 W, 8 Ω

- 25 mm (1") compression driver with 25 mm (1") voice coil and ferrite magnet
- One-piece PETP cone and surround
- Recommended crossover frequency: 2,200 Hz (12 dB/oct.)
- 2-hole screw mounting

Manufacturer information:
Celestion International Ltd
Claydon Business Park, Great Blakenham,
Ipswich
Suffolk IP6 0NL
United Kingdom
info@celestion.com

Importer:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen

Deutschland
info@monacor.com

SPECIFICATIONS

CDX1-1070/8

Impedance (Z)	8 Ω
Transmission technology	cable
Frequency range	1,500-20,000 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	2,200 Hz
Power rating (RMS)	12 W
Peak music power output (MAX)	24 W
SPL	106 dB/W/m
Voice coil diameter	Ø 25 mm
Voice coil material	flat copper-coated aluminium wire
Voice coil former	PETP
Outlet	25 mm
Mounting cutout	dep. on horn
Mounting depth	dep. on horn
Mounting hole diameter	Ø 76 mm (2-hole)
Dimensions	Ø 70 mm x 50 mm
Outside diameter	Ø 70 mm
Width	Ø 70 mm
Height	Ø 70 mm
Depth	50 mm
Colour	black/silver
Admiss. ambient temp.	0-40 °C
Weight	0.5 kg
Packing unit	1
Type of speaker	1"
Packaging dimensions (W x H x L)	0.095 x 0.065 x 0.095 m
Gross weight	0.57 kg
Net weight	0.5 kg

CDX1-1070/8

EAN code	0739894591645
Net weight	0.5 kg