

CDX1-1446/8

Order no.: 1001101

PRODUCT INFORMATION

PA horn driver, 20 W, 8 Ω

- High-quality 25 mm (1") compression driver with 35 mm (1.4") voice coil and ferrite magnet
- One-piece PETP cone and surround
- Integrated cone and rear cover for easy replacement
- Recommended crossover frequency: 2,200 Hz (12 dB/oct.)
- 35 mm standard thread (1⅜")

Manufacturer information:
Celestion International Ltd
Claydon Business Park, Great Blakenham,
Ipswich
Suffolk IP6 0NL
United Kingdom
info@celestion.com

Importer:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68

28217 Bremen
Deutschland
info@monacor.com

SPECIFICATIONS

CDX1-1446/8

Impedance (Z)	8 Ω
Transmission technology	cable
Frequency range	1,500-20,000 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	2,200 Hz
Power rating (RMS)	20 W
Peak music power output (MAX)	40 W
SPL	106 dB/W/m
Voice coil diameter	Ø 35 mm
Voice coil material	flat copper-coated aluminium wire
Outlet	Ø 25 mm
Mounting cutout	dep. on horn
Mounting depth	dep. on horn
Dimensions	Ø 90 mm x 52 mm
Outside diameter	Ø 90 mm
Width	Ø 90 mm
Height	Ø 90 mm
Depth	52 mm
Colour	black
Admiss. ambient temp.	0-40 °C
Weight	1.0 kg
Packing unit	1
Type of speaker	1"
Packaging dimensions (W x H x L)	0.13 x 0.081 x 0.11 m
Gross weight	1.2 kg
Net weight	1.0 kg

CDX1-1446/8

EAN code	0739894579650
Net weight	1.0 kg