

CDX1-1745/8

Order no.: 1001104

PRODUCT INFORMATION

PA horn driver, 40 W, 8 Ω

- High-quality 25 mm (1") compression driver with 44 mm (1.75") voice coil and ferrite magnet
- One-piece polyamide cone and surround
- Sound castle cone arrangement
- Recommended crossover frequency: 2,200 Hz (12 dB/oct.)
- 2-hole and 3-hole screw mounting
- Also available as 16 Ω version (CDX1-1745/16) or with 35 mm standard thread (CDX1-1746/8)

Manufacturer information:
Celestion International Ltd
Claydon Business Park, Great Blakenham,
Ipswich
Suffolk IP6 0NL
United Kingdom
info@celestion.com

Importer:

MONACOR INTERNATIONAL GmbH & Co. KG

Konsul-Smidt-Str. 68
28217 Bremen
Deutschland
info@monacor.com

SPECIFICATIONS

CDX1-1745/8	
Impedance (Z)	8 Ω
Transmission technology	cable
Frequency range	1,200-20,000 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	2,200 Hz
Power rating (RMS)	40 W
Peak music power output (MAX)	80 W
SPL	110 dB/W/m
Voice coil diameter	Ø 44 mm
Voice coil material	flat copper-coated aluminium wire
Outlet	Ø 25 mm
Mounting cutout	dep. on horn
Mounting depth	dep. on horn
Mounting hole diameter	Ø 76 mm (2x M6), Ø 57 mm (3x M6)
Dimensions	Ø 120 mm x 56 mm
Outside diameter	Ø 120 mm
Width	Ø 120 mm
Height	Ø 120 mm
Depth	56 mm
Colour	black
Admiss. ambient temp.	0-40 °C
Weight	1.96 kg
Packing unit	1
Type of speaker	1"
Packaging dimensions (W x H x L)	0.135 x 0.07 x 0.175 m
Gross weight	2.1 kg
Net weight	1.96 kg

CDX1-1745/8

EAN code	0739894536349
Net weight	1.96 kg