

CDX14-2420/8

Order no.: 1001073

PRODUCT INFORMATION

PA horn driver, 70 W, 8 Ω

- High-quality 35 mm (1.4") compression driver with 60 mm (2.4") voice coil and neodymium magnet
- Phase plug with maximum modal suppression
- Deep-drawn titanium cone and ploymide surround
- Recommended crossover frequency: 1,200 Hz (12 dB/oct.)

Manufacturer information:
Celestion International Ltd
Claydon Business Park, Great Blakenham,
Ipswich
Suffolk IP6 0NL
United Kingdom
info@celestion.com

Importer:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68

28217 Bremen
Deutschland
info@monacor.com

SPECIFICATIONS

CDX14-2420/8

Impedance (Z)	8 Ω
Transmission technology	cable
Frequency range	800-20,000 Hz
Rec. crossov. frequ. (fmax.) (12 dB/oct.)	1,200 Hz
Power rating (RMS)	70 W
Peak music power output (MAX)	140 W
SPL	106.5 dB/W/m
Voice coil diameter	Ø 60 mm
Voice coil material	flat copper-coated aluminium wire
Outlet	Ø 36 mm
Mounting cutout	dep. on horn
Mounting depth	dep. on horn
Mounting hole diameter	Ø 102 mm (4 x M6)
Dimensions	Ø 116 mm x 56 mm
Outside diameter	Ø 116 mm
Width	Ø 116 mm
Height	Ø 116 mm
Depth	56 mm
Colour	black
Admiss. ambient temp.	0-40 °C
Weight	1.75 kg
Packing unit	1
Type of speaker	1.4"
Packaging dimensions (W x H x L)	0.135 x 0.07 x 0.175 m
Gross weight	1.91 kg
Net weight	1.75 kg

CDX14-2420/8

EAN code	0739894577946
Net weight	1.75 kg