

CF0617M/8

Order no.: 1001121

PRODUCT INFORMATION

PA midrange speaker, 200 W, 8 Ω

- Inverse dust cap allows for tight positioning of a phase plug, e.g. with horn applications
- Long-term stable, temperature-resistant, flat foam surround
- Ideally suited for multi-way PA systems, high-quality studio monitors and hi-fi

Manufacturer information:
Celestion International Ltd
Claydon Business Park, Great Blakenham,
Ipswich
Suffolk IP6 0NL
United Kingdom
info@celestion.com

Importer:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Deutschland

info@monacor.com

SPECIFICATIONS

CF0617M/8

Impedance (Z)	8 Ω
Transmission technology	cable
Frequency range	300-7,000 Hz
Resonant frequency (fs)	116.6 Hz
Power rating (RMS)	200 W
Peak music power output (MAX)	400 W
SPL	96 dB/W/m
Suspension compl. (Cms)	0.1 mm/N
Moving mass (Mms)	11.5 g
Mech. Q factor (Qms)	6,93
Electr. Q factor (Qes)	0,481
Total Q factor (Qts)	0,451
Equivalent volume (Vas)	5.4 l
DC resistance (Re)	5.3 Ω
Force factor (BxL)	9 Tm
Voice coil induct. (Le)	1.73 mH
Voice coil diameter	Ø 45 mm
Voice coil winding height	8.4 mm
Voice coil material	flat copper-coated aluminium wire
Voice coil former	glass fibre
Linear excursion (XMAX)	± 2.7 mm
Eff. cone area (Sd)	153.9 cm^2
Magnet weight	0.6 kg
Mounting cutout	Ø 150 mm
Mounting depth	78.5 mm
Mounting hole diameter	173-175 mm
Dimensions	189 x 189 x 78.5 mm
Width	189 mm
Height	189 mm
Depth	78.5 mm
Colour	black
Admiss. ambient temp.	0-40 °C

CF0617M/8

Weight	1.9 kg
Packing unit	1
Type of speaker	6.5"
Packaging dimensions (W x H x L)	0.19 x 0.11 x 0.19 m
Gross weight	2.5 kg
Net weight	1.9 kg

CF0617M/8

EAN code	739894588652
Net weight	1.9 kg