

CM-214ULF

Order no.: 0236450

PRODUCT INFORMATION

Electret headband microphone

- Transparent sound
- Adjustable headband, comfortable to wear
- Highly resistant to acoustic feedback due to cardioid polar pattern
- Replaceable connection cable
- Flexible cartridge arm for exact positioning of cartridge, thus providing an optimum sound with an unobtrusive appearance
- Connection cable with strain relief, screwed-on
- Integrated drip ring protects the cartridge from moisture
- Supplied with a 4-pole mini XLR connection cable for connection to pocket transmitters of the IN/PT/UF series
- Connection cable 801TG with 3.5 mm plug for use with our tour guide systems is available at option
- Supplied with bag and windshield

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City

Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

CM-214ULF	
Description	headband microphone
Transmission method	cable
Polar pattern	cardioid
System	electret
Audio frequency range	100-18,000 Hz
Nominal impedance	1.5 kΩ
Sensitivity	1.8 mV/Pa
Max. sound pressure	120 dB
Power supply	JTS UHF PLL Pocket Transmitter
Admiss. ambient temp.	0-40 °C
Weight	44 g
Connection	4-pole mini XLR (optional: 3.5 mm stereo plug, 3-pole mini XLR or 4-pole Hirose connector)
Packaging dimensions (W x H x L)	0.145 x 0.1 x 0.185 m
Gross weight	0.189 kg
Net weight	0.048 kg

CM-214ULF	
EAN code	4007754242966
Net weight	0.048 kg