

CM-503N/W

Order no.: 0231730

PRODUCT INFORMATION

Built-in electret microphone

- Omnidirectional microphone cartridge
- Compact boundary microphone
- Low-cut switch (80 Hz)
- Switchable 10 dB attenuation
- Metal housing
- White cartridge cover

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68

28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

CM-503N/W

Description	built-in microphone
Transmission method	cable
Polar pattern	omnidir.
System	electret
Audio frequency range	40-17,000 Hz
Nominal impedance	220 Ω
Sensitivity	4 mV/Pa
S/N ratio	68 dB
Max. sound pressure	140 dB
Power supply	DC 9-52 V, phantom power
Housing material	metal
Admiss. ambient temp.	0-40 °C
Dimensions	31.6 x 69.7 x 30 mm
Weight	67 g
Connection	XLR, bal.
Packaging dimensions (W x H x L)	0.07 x 0.045 x 0.14 m
Gross weight	0.137 kg
Net weight	0.1 kg

CM-503N/W

EAN code	4007754247978
Net weight	0.1 kg