

CM-601

Order no.: 0235010

PRODUCT INFORMATION

Electret boundary microphone

- For theatrical performances, discussions, conferences and in churches
- A direct alignment to the sound source is not essential due to the special characteristics of a boundary microphone
- Dual low cut filter (80 Hz/120 Hz)
- Configurable push-button (PTT, PTM or switching function)
- Standby LED
- Robust and shock-absorbing body
- Elastic cartridge suspension for preventing structure-borne noise and impact sound
- With 8 m cable mini XLR jack to XLR plug
- Connection via 3-pole mini XLR plug, bal.
- With preformed outline at the bottom for possible wall mounting

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

CM-601

Description	boundary microphone
Transmission method	cable
Polar pattern	semi-cardioid
System	electret
Audio frequency range	30-12,000 Hz
Nominal impedance	100 Ω
Sensitivity	2.2 mV/Pa
Max. sound pressure	125 dB
Power supply	DC 15-48 V, phantom power
Housing material	diecast metal
Admiss. ambient temp.	0-40 °C
Dimensions	72 x 22.5 x 110 mm
Weight	0.85 kg
Cable	8 m, mini XLR/XLR
Connection	3-pole mini XLR plug, bal.
Packaging dimensions (W x H x L)	0.155 x 0.06 x 0.16 m
Gross weight	0.399 kg
Net weight	0.269 kg

CM-601

Width	72.5 mm
Height	22 mm
Depth	110 mm
Weight	0.85 kg

CM-601

EAN code	4007754194487
Net weight	0.269 kg