

MADE IN GERMANY

CTG-1NOISE

Order no.: 0292050

PRODUCT INFORMATION

XLR function tester, 48 V,
with integrated pink noise generator.

- For an easy and fast functional test of balanced microphone cables or of microphone inputs on stage
- Visual fault indication via LED

- Flashing twice: pin 2 of XLR cable is defective
- Flashing three times: pin 3 of XLR cable is defective
- LED is off: pin 1 or phantom power is defective
- LED is lighting up permanently: faultless cable, noise generator

- 3-pole XLR plug
- Power supply via phantom power: 9-48 V
- Output amplitude: 100 mV_{pp}
- Dimensions: Ø 19 mm x 74 mm
- Weight: 31 g

SOUNDCHECK 05/2013
“Useful tools for practical applications. The CTG testers (CTG-1NOISE & CTG-1SINE) are beneficial for stagehands who frequently have to search for the reason why there is no incoming signal.”
+ Extra compact size
+ Reliable operation
+ Visual and acoustic indication

tools4music 03/2012

“The optogate phantom power line tester and the pink noise generator are ideally suited for applications on stage and in front of it. Anyone insisting on useful tools will love it. Totally recommendable. With both test candidates, a line check is far quicker and equally reliable. The visual and acoustic indications ensure a quick and reliable operation on stage - an absolute advantage.”

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

CTG-1NOISE	
Description	XLR function tester
Nominal value	48 V
Type	with integrated pink noise generator
Colour	chrome/black
Suitable for	balanced microphone cables, microphone inputs
Power supply	phantom power: 9-48 V
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 19 mm x 74 mm
Weight	31 g

CTG-1NOISE

Connections	3-pole XLR plug
Packing unit	1
Packaging dimensions (W x H x L)	0.08 x 0.02 x 0.15 m
Gross weight	0.041 kg
Net weight	0.031 kg

CTG-1NOISE

EAN code	4007754227826
Net weight	0.031 kg