

DAR-1000-10

Order no.: 1001455

PRODUCT INFORMATION

PA wall and ceiling speaker

- 100 V transmission technology via audio transmitter with 3-step power taps
- High performance full range speaker (20 cm) with very high sound pressure (96 dB/1 W/1 m)
- White metal housing with metal protective grille
- Supplied with mounting material

Manufacturer information:
PÖSCHEL ETG e.K.
Mäuswedel 11
74223 Flein
Deutschland
info@poeschel-etg.de

SPECIFICATIONS

DAR-1000-10	
Active/passive	passive
Transmission technology	100 V

DAR-1000-10

Total power rating	10 W
Power rating (RMS)	10/5/2.5 W
Frequency range	100-18,000 Hz
Number of speakers	1
Speaker size	20 cm (8")
SPL	96 dB/W/m
Max. rated SPL	105 dB
Radiation angle/beam angle	180° (500 Hz) 160° (1 kHz) 160° (2 kHz) 140° (4 kHz)
Radiation angle, horizontal	180° (500 Hz) 160° (1 kHz) 160° (2 kHz) 140° (4 kHz)
Radiation angle, vertical	180° (500 Hz) 160° (1 kHz) 160° (2 kHz) 140° (4 kHz)
Housing material	metal
Colour	White, RAL 9010
Mounting device	Aluminium bracket
Dimensions	Ø 220 mm x 100 mm
Width	Ø 220 mm
Height	Ø 220 mm
Depth	100 mm
Weight	2 kg
Inputs	pressure clamps
Packaging dimensions (W x H x L)	0.225 x 0.225 x 0.11 m
Gross weight	2.1 kg
Net weight	2 kg

DAR-1000-10

EAN code	4007754429893
Net weight	2 kg