DIB-100

Order no.: 0241140

PRODUCT INFORMATION

DI Boxes
For an optimum signal transmission from musical instruments to a mixer or amplifier. By using a transformer coupling, interferences due to matching problems, e.g. hum loops, are prevented to a large extent. Input and output are galvanically isolated.

For adapting line levels, please use units of the LTR series!

DI box

- 3-fold attenuation switch (0/-20/-40 dB)
- Ground lift switch
- Instrument feed-through output
- Wideband balancing transformer
- Robust metal housing

PRODUCTION PARTNER 04/2013
“The measured values and workmanship give no reason for criticism. When considering the price, too, you can't go wrong.”

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

DIB-100

Description	DI box
Frequency range	15-30,000 Hz
Input impedance	50 kΩ
Output impedance	600 Ω (bal.), 50 kΩ (unbal.)
Gain	0/-20/-40 dB
Transmission ratio	10:1
Admiss. ambient temp.	0-40 °C
Dimensions	74 x 45 x 130 mm
Weight	560 g
Inputs	1 x 6.3 mm jack, unbal
Outputs	1 x 6.3 mm jack, unbal., par. out XLR, bal.

DIB-100

Width	74 mm
Height	45 mm
Depth	130 mm
Weight	0.56 kg

DIB-100

EAN code	4007754004021
Net weight	0.56 kg