DIB-102

Order no.: 0247060

PRODUCT INFORMATION

DI Boxes
For an optimum signal transmission from musical instruments to a mixer or amplifier. By using a transformer coupling, interferences due to matching problems, e.g. hum loops, are prevented to a large extent. Input and output are galvanically isolated.

For adapting line levels, please use units of the LTR series!

2-channel DI box

- 3-fold attenuation switch (0/-20/-40 dB) for each channel
- 1 ground lift switch for each channel
- 1 instrument feed-through output for each channel
- Wideband balancing transformer
- Robust metal housing

tools4music 06/2009
on the LSP-102, LC-31, FGA-102, FGA-202, DIB-102
“Recommendable and fit for on-the-road applications. An attractively priced little audio aid, perfect for the 'ever accompanying' tool case.”

tools4music 02/2010
“The DIB-102 from IMG Stage Line impresses by both the attractive price and the very stable housing. The frequency curve is exemplary.”

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

DIB-102

Description	DI box
Frequency range	15-30,000 Hz
Input impedance	50 kΩ
Output impedance	600 Ω, XLR50 kΩ, jack
Transmission ratio	10:1
Admiss. ambient temp.	0-40 °C
Dimensions	148 x 50 x 130 mm
Weight	755 g
Inputs	2 x 6.3 mm jack, unbal.
Outputs	2 x 6.3 mm jack, unbal.,par. out2 x XLR, bal.

DIB-102

Width	148 mm
Height	50 mm
Depth	130 mm
Weight	0.755 kg

DIB-102

EAN code	4007754131840
Net weight	0.755 kg