

Exclusive FOR CERTIFIED PARTNERS

DRM-884IOP

Order no.: 0176960

PRODUCT INFORMATION

The versatile audio matrix system DRM-884 ...
A general solution for versatile multi-room PA concepts with fixed installations in hotels, restaurants and bars, conference rooms, schools, sports and fitness centres.

The matrix system DRM-884 is a professional tool with extensive features which easily meets any requirement: users can combine signal sources, play one source in several zones or several sources in one zone, adjust the volume in each zone and much more. The audio matrix router DRM-884 is the heart of the system which is able to distribute a maximum of 8 analogue and 4 digital audio sources to just as many output zones, any assignment possible. You can either connect active speakers or a power amplifier with passive speakers to the output zones via Phoenix terminals.

The multifunctional matrix system is controlled via wall panels: modules DRM-884VAP and DRM-884VP allow you to remotely access, e.g. level and program selection in the different zones. The wall panel DRM-884IOP allows for other connection options are available, e.g. at the location of the PA application. The zone paging microphone DRM-884RC with zone selection can be connected for announcements.

Expand your options with the matrix system: if you need a larger number of inputs and outputs, the system can be extended from a maximum of 16 x DRM-884 and optional Dante® module to 192 inputs x 192 outputs by means of cascading.

With the Dante® extension module DRM-884DTM, the DRM-884 can quickly and easily be inserted into a Dante® audio network. For this purpose, there are an additional 8 digital inputs or 8 digital outputs available which can be assigned to either an analogue output or a Dante® channel.

Wall module,
for remote control of audio matrix router DRM-884.

- Intended application: remote control of one zone, local insertion of audio signals
- 2 RCA jacks for line signals
- Adjustable microphone connection via NEUTRIK 3-pole XLR jack
- 48 V phantom power, to be activated as required
- LED indication for input signals and output signals
- Connection to DMR-884 and power supply via RJ45 jack and Cat. 5 network cable, cable length up to 100 m

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety and warning notices
Only use the device indoors and protect it from dripping and splashing water, high humidity and heat (permissible operating temperature range 0 - 40 °C).
Do not operate the appliance if there is visible damage to the appliance, if a defect is suspected after a fall or similar, or if malfunctions occur. Always return the appliance to a specialised workshop for repair.
If the appliance is to be taken out of service permanently, hand it over to a local recycling centre for environmentally friendly disposal.

SPECIFICATIONS

DRM-884IOP	
Description	wall module
Type	remote control of one zone

DRM-884IOP

Colour	white
Material	plastic
Suitable for	DRM-884
Power supply	via DRM-884
Admiss. ambient temp.	0-40 °C
Dimensions	145 x 85 x 53 mm
Weight	293 g
Connections	1 x XLR (microphone), 1 x RCA L/R (line), 1 x RJ45
Other features	48 V phantom power
Packing unit	1
Packaging dimensions (W x H x L)	0.125 x 0.095 x 0.185 m
Gross weight	0.396 kg
Net weight	0.293 kg

DRM-884IOP

EAN code	4007754261790
Net weight	0.293 kg