

EDL-165C/WS

Order no.: 0160090

PRODUCT INFORMATION

PA ceiling speaker,
with EN 54-24 certification.

- 100 V transmission technology
- Full range speaker with a high efficiency
- Metal housing
- Fire protection cover
- Quick mounting facility
- 3 power taps via push terminals
- Ball-proof according to DIN 18032, Part 3
- Connection via 4-pole ceramic terminal

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

EDL-165C/WS

Transmission technology	100 V
Frequency range	80-19,000 Hz
Power rating (RMS)	6/3/1.5 W
SPL	93 dB (1 W/1 m) 78 dB (EN, 1 W/4 m)
Max. rated SPL	101 dB (1 m) 86 dB (EN, 4 m)
Radiation angle, horizontal	180° (500 Hz) 180° (1 kHz) 155° (2 kHz) 76° (4 kHz)
Radiation angle, vertical	180° (500 Hz) 180° (1 kHz) 155° (2 kHz) 76° (4 kHz)
Mounting cutout	Ø 150 mm
Mounting depth	90 mm
Dimensions	Ø 170 mm x 95 mm
Outside diameter	Ø 170 mm
Width	Ø 170 mm
Height	Ø 170 mm
Depth	95 mm
Colour	white
Admiss. ambient temp.	0-40 °C
Weight	1.1 kg
Packing unit	1
Type of speaker	130
Packaging dimensions (W x H x L)	0.195 x 0.1 x 0.195 m
Gross weight	1.26 kg
Net weight	1.16 kg

EDL-165C/WS

EAN code	4007754233346
Net weight	1.16 kg