

EDL-70/WS

Order no.: 0163310

PRODUCT INFORMATION

PA ceiling speaker,
with special 2-step mounting.

- 100 V transmission technology
- Snap-in mounting
- For a ceiling thickness from 2 to 45 mm
- Full range speaker with a clear voice reproduction
- Wide frequency range
- Robust metal version (basket and protective grille)

For mounting this PA ceiling speaker, the mounting frame is attached to the ceiling cutout at first via the snap-in system. Then, the speaker is inserted into the frame with a bayonet-type locking. A safety rope provides additional safety.

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

EDL-70/WS

Transmission technology	100 V
Frequency range	90-20,000 Hz
Power rating (RMS)	6/3/1.5 W
SPL	97 dB/W/m
Mounting cutout	Ø 195 mm
Mounting depth	100 mm
Dimensions	Ø 220 mm x 104 mm
Outside diameter	Ø 220 mm
Width	Ø 220 mm
Height	Ø 220 mm
Depth	104 mm
Colour	white, RAL9010
Admiss. ambient temp.	0-40 °C
Weight	1 kg
Packing unit	1
Type of speaker	165
Packaging dimensions (W x H x L)	0.225 x 0.115 x 0.225 m
Gross weight	1.127 kg
Net weight	1.017 kg

EDL-70/WS

EAN code	4007754244472
Net weight	1.017 kg