

ESP-72/WS

Order no.: 0162130

PRODUCT INFORMATION

PA wall speaker

- 100 V transmission technology
- 2-way coaxial speaker, providing a high-quality sound
- 5-step rotary switch for 20/10/5/2.5 W/off
- Rotary switch can be replaced with a cover plate to avoid accidental changing of the power selection
- Emergency priority relay
- White wooden cabinet with protective metal grille
- Mounting plate for easy wall mounting
- Ball-proof according to DIN 18032, Part 3

- PA wall speaker

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany

info@monacor.com

SPECIFICATIONS

ESP-72/WS

Active/passive	passive
Transmission technology	100 V
Total power rating	20 W
Power rating (RMS)	20/10/5/2.5 W
Frequency range	85-20,000 Hz
Number of speakers	2
Speaker size	16 cm (6.5")
Radiation angle/beam angle	H: 120°/V: 120°
Radiation angle, horizontal	120°
Radiation angle, vertical	120°
Housing material	wood
Colour	white
Mounting device	mounting plate
Protected against ball rebound	yes
Admiss. ambient temp.	0-40 °C
Dimensions	300 x 200 x 90 mm
Width	300 mm
Height	200 mm
Depth	90 mm
Weight	2.8 kg
Inputs	screw terminals
Packaging dimensions (W x H x L)	0.11 x 0.23 x 0.32 m
Gross weight	3.02 kg
Net weight	2.82 kg

ESP-72/WS

EAN code	4007754195668
Net weight	2.82 kg