

ETS-515TW/WH

Order no.: 1001314

PRODUCT INFORMATION

PA column speaker

- 100 V transmission technology or 8 Ω operation
- 2-way version (with additional integrated tweeter for a clearly improved sound)
- Integrated crossover network
- 6-step power selector switch with 8 Ω selection
- 2 x 6 mm threaded bushing
- Plastic cabinet and speaker grille cloth
- Supplied with end-to-end mounting bracket
- Terminal strip connection

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

ETS-515TW/WH

Active/passive	passive
Transmission technology	100 V or low-impedance
Total power rating	30 W
Power rating (RMS)	15/7.5/4/2/1 W (100 V) 15 W (8 Ω)
Impedance	8 Ω
Frequency range	90-20,000 Hz
System	2-way
Number of speakers	2+1
Speaker size	10 cm (4")
SPL	87 dB/W/m
Radiation angle/beam angle	H: 140°/V: 50°
Radiation angle, horizontal	140°
Radiation angle, vertical	50°
Housing material	plastic
Colour	white
Mounting device	mounting bracket, end-to-end
Admiss. ambient temp.	0-40 °C
Dimensions	128 x 385 x 140 mm
Width	128 mm
Height	385 mm
Depth	140 mm
Weight	2.8 kg
Inputs	plug-in screw terminals
Packaging dimensions (W x H x L)	0.18 x 0.18 x 0.5 m
Gross weight	3.1 kg
Net weight	2.84 kg

ETS-515TW/WH

EAN code	4007754428032
Net weight	2.84 kg