

ETS-530TW/SW

Order no.: 0162650

PRODUCT INFORMATION

PA column speaker

- 100 V transmission technology or 8 Ω operation
- 2-way version (with additional integrated tweeter for a clearly improved sound)
- Integrated crossover network
- 6-step power selector switch with 8 Ω switching
- 2 x 6 mm threaded bushing
- Plastic cabinet and protective metal grille in black (SW) or white (WS)
- Supplied with mounting brackets
- Connection via spring-loaded speaker terminal

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

ETS-530TW/SW

Active/passive	passive
Transmission technology	100 V or low-impedance
Total power rating	60 W
Power rating (RMS)	30/15/7.5/4/2 W (100 V) 30 W (8 Ω)
Impedance	8 Ω
Frequency range	85-20,000 Hz
System	2-way
Number of speakers	4+1
Speaker size	10 cm (4")
SPL	89 dB/W/m
Radiation angle/beam angle	H: 140°/V: 40°
Radiation angle, horizontal	140°
Radiation angle, vertical	40°
Housing material	plastic
Colour	black
Mounting device	mounting bracket
Admiss. ambient temp.	0-40 °C
Dimensions	128 x 620 x 140 mm
Width	128 mm
Height	620 mm
Depth	140 mm
Weight	4.5 kg
Inputs	spring-load. term.
Packaging dimensions (W x H x L)	0.18 x 0.18 x 0.73 m
Gross weight	4.94 kg
Net weight	4.56 kg

ETS-530TW/SW

EAN code	4007754214246
Net weight	4.56 kg