FGA-202

Order no.: 0251660

PRODUCT INFORMATION

Professional 2-channel line transformer,
for reducing signal interference and hum loops.

- 2 inputs via balanced comb. jacks XLR/6.3 mm (600 Ω)
- 2 galvanically isolated XLR outputs (600 Ω) with ground lift switch
- Frequency range: 20-20,000 Hz
- Robust metal housing with very good shielding qualities, suitable for stage applications
- Dimensions: 125 x 55 x 75 mm
- Weight: 650 g

SOUNDCHECK 07/2007
on the FGA-102, FGA-202, LC-31, MC-31 and LSP-102:
“Every musician or sound engineer should have these little helpers in their toolbox. They impress by their unobtrusiveness. Both the robust metal housing and the functionality of these transformers allow to solve many problems on stage or in the studio at a reasonable price.”

tools4music 06/2009
on the LSP-102, LC-31, FGA-102, FGA-202, DIB-102
“Recommendable and fit for on-the-road applications. An attractively priced little audio aid, perfect for the 'ever accompanying' tool case.”

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

FGA-202

Description	transformer
Frequency range	20-20,000 Hz
Input impedance	600 Ω
Output impedance	600 Ω
Admiss. ambient temp.	0-40 °C
Dimensions	125 x 55 x 75 mm
Weight	650 g
Inputs	2 x comb. jack XLR/6.3 mm, bal.
Outputs	2 x XLR

FGA-202

EAN code	4007754197709
Net weight	0.652 kg