

GLS-301/GR

Order no.: 0163070

PRODUCT INFORMATION

Weatherproof PA garden speaker 'Rock',
stone look, for general PA applications, e.g. in gardens, hotels, restaurants and pubs.

- Omnidirectional radiation
- 100 V transmission technology or 8 Ω operation
- Robust, glass fibre reinforced plastic cabinet
- Full range speaker (200 mm)
- Integrated audio transformer with 4 power taps (30/20/10/5 W)
- Connection cable with luster terminals

Note: the colour of the product shown may not match the original colour due to lighting conditions during product photography and different screen settings.

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

GLS-301/GR

Active/passive	passive
Transmission technology	100 V or low-impedance
Total power rating	90 W
Power rating (RMS)	30/20/10/5 W (100 V) 45 W (8 Ω)
Impedance	8 Ω
Frequency range	60-20,000 Hz
System	full range speaker
Number of speakers	2
Speaker size	20 cm (8")
SPL	89 dB/W/m
Radiation angle/beam angle	360°
Radiation angle, horizontal	360°
Radiation angle, vertical	360°
Housing material	GRP
Colour	light grey
Protection class	IP52
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	320 x 500 x 310 mm
Width	320 mm
Height	500 mm
Depth	310 mm
Weight	10.1 kg
Inputs	cable connection, screw terminals
Packaging dimensions (W x H x L)	0.375 x 0.58 x 0.4 m
Gross weight	11.4 kg
Net weight	10.1 kg

GLS-301/GR

EAN code	4007754227550
Net weight	10.1 kg