

# GM-5212LDU

Order no.: 0236290

## PRODUCT INFORMATION

**Double gooseneck microphones with LED**

- Back electret supercardioid cartridges
- High sensitivity
- 10 dB attenuator
- Low cut switch
- LED for indicating operating status
- Flexible positioning due to vertically adjustable goosenecks (160°)
- Common 3-pole XLR plug
- Operation via +48 V phantom power

**Manufacturer information:**
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

**EU-Representative:**

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

## SPECIFICATIONS

**GM-5212LDU**

| | |
|---|---|
| Description | gooseneck microphone |
| Version | double, LED |
| Transmission method | cable |
| Polar pattern | supercardioid |
| System | back electret |
| Audio frequency range | 80-18,000 Hz |
| Nominal impedance | 220 Ω |
| Sensitivity | 16 mV/Pa |
| Max. sound pressure | 125 dB |
| Power supply | DC 48 V phantom power |
| Admiss. ambient temp. | 0-40 °C |
| Dimensions | 415 mm |
| Weight | 315 g |
| Connection | XLR, bal. |
| Packaging dimensions (W x H x L) | 0.09 x 0.04 x 0.5 m |
| Gross weight | 0.475 kg |
| Net weight | 0.315 kg |

**GM-5212LDU**

| | |
|---|---|
| EAN code | 4007754234121 |
| Net weight | 0.315 kg |