

# GM-5212SW

Order no.: 1000894

## PRODUCT INFORMATION

**Electret gooseneck microphone with on/off push-button**

- Supercardioid polar pattern
- Natural sound, precise voice reproduction
- Low susceptibility to acoustic feedback
- LED for indicating operating status
- Silent on/off push-button
- Reliable and high-quality workmanship for a long service life
- Gooseneck with integrated 3-pole XLR plug
- Operation via external phantom power supply or desktop base
- Supplied with windshield

**Manufacturer information:**
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

**EU-Representative:**

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

## SPECIFICATIONS

**GM-5212SW**

| | |
|---|---|
| Description | gooseneck microphone |
| Version | LED |
| Transmission method | cable |
| Polar pattern | supercardiod |
| System | back electret |
| Audio frequency range | 80-18,000 Hz |
| Nominal impedance | 100 Ω |
| Sensitivity | 15.8 mV/Pa |
| S/N ratio | 74 dB |
| Max. sound pressure | 125 dB |
| Power supply | DC 12-48 V phantom power |
| Gooseneck length | 305 mm |
| Admiss. ambient temp. | 0-40 °C |
| Dimensions | 466 mm |
| Weight | 180 g |
| Connection | XLR, bal. |
| Packaging dimensions (W x H x L) | 0.495 x 0.091 x 0.059 m |
| Gross weight | 0.33 kg |
| Net weight | 0.18 kg |

**GM-5212SW**

| | |
|---|---|
| EAN code | 4007754419399 |
| Net weight | 0.18 kg |