

GM-5215LDU

Order no.: 0236310

PRODUCT INFORMATION

Double gooseneck microphones with LED

- Back electret supercardioid cartridges
- High sensitivity
- 10 dB attenuator
- Low cut switch
- LED for indicating operating status
- Flexible positioning due to vertically adjustable goosenecks (160°)
- Common 3-pole XLR plug
- Operation via +48 V phantom power

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

GM-5215LDU

Description	gooseneck microphone
Version	double, LED
Transmission method	cable
Polar pattern	supercardioid
System	back electret
Audio frequency range	80-18,000 Hz
Nominal impedance	220 Ω
Sensitivity	16 mV/Pa
Max. sound pressure	125 dB
Power supply	DC 48 V phantom power
Admiss. ambient temp.	0-40 °C
Dimensions	492 mm
Weight	335 g
Connection	XLR, bal.
Packaging dimensions (W x H x L)	0.09 x 0.04 x 0.66 m
Gross weight	0.53 kg
Net weight	0.335 kg

GM-5215LDU

EAN code	4007754234145
Net weight	0.335 kg