

JS-22

Order no.: 0231970

PRODUCT INFORMATION

Professional condenser microphone,
for studio applications and live performances. Ideally suited for direct or overhead sound pickup of acoustic instruments, percussions and vocals or 2 x JS-22 for high-quality stereo recordings.

- 1.25 cm (½") extra thin gold-plated diaphragm
- Low cut switch (80 Hz)
- 10 dB attenuation, switchable
- 48 V phantom power
- Robust brass body of high quality
- Supplied accessories: robust hard-sided case, microphone windshield and microphone holder

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

JS-22

Description	condenser microphone
Transmission method	cable
Polar pattern	cardioid
System	condenser
Audio frequency range	20-20,000 Hz
Nominal impedance	100 Ω
Sensitivity	15.8 mV/Pa
S/N ratio	78 dB
Max. sound pressure	140 dB
Power supply	DC 48 V, phantom power
Housing material	brass
Admiss. ambient temp.	0-40 °C
Dimensions	Ø 20 mm x 150 mm
Weight	130 g
Connection	XLR, bal.
Packaging dimensions (W x H x L)	0.172 x 0.09 x 0.37 m
Gross weight	0.866 kg
Net weight	0.615 kg

JS-22

EAN code	4007754244854
Net weight	0.615 kg