

KA-10/1PACK

Order no.: 0253120

PRODUCT INFORMATION

Wireless 16-channel PLL audio transmission system for cameras

- Consisting of a portable audio transmitter and receiver
- Carrier frequency range: 863-865 MHz
- Transmitter and receiver with rechargeable lithium-ion batteries for reducing the weight and to ensure long operating times
- Transmitter can also be used for transmitting line signals (adjustment via recessed gain control)
- Receiver with 3-step PAD switch (0dB/-10 dB/-20 dB) for perfect level matching to the audio input of the camera
- Transmitter and receiver are fitted with a robust metal fixing clip
- Operating time: approx. 12 hours
- Supplied with lavalier microphone in skin design with windshield and tie clip, attachment clip for camera mounting, trim key, dual charging slot with plug-in switch-mode power supply, connection cable with 3.5 mm plug to 3.5 mm plug, connection cable with 3.5 mm plug to XLR plug
- Connection cable 801TG with 3.5 mm plug is available at option for certain JTS headband microphones

Licence-free in the EU.

Supplied w/o camera.

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.
Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.
Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

SPECIFICATIONS

KA-10/1PACK

General information

Description	16-channel PLL audio transmission system
Carrier frequency range	863-865 MHz
Audio frequency range	40-18,000 Hz
Channels	1
THD	< 1%

KA-10/1PACK

Operating time	< 12 h
Admiss. ambient temp.	0-40 °C

Specifications transmitter

Transmitting power	< 10 mW
Operating range	approx. 60 m
Power supply transmitter	3.7 V rech. lithium-ion battery
Width transmitter	55 mm
Height transmitter	100 mm
Depth transmitter	18 mm
Weight transmitter	80 g

Specifications receiver

Audio signal receiver	300 mV/7 kΩ (jack)
Power supply receiver	3.7 V rech. lithium-ion battery
Width receiver	55 mm
Height receiver	100 mm
Depth receiver	18 mm
Weight receiver	82 g
Connections receiver	1 x 3.5 mm jack (transmitter)1 x 3.5 mm jack (receiver)

KA-10/1PACK

EAN code	4007754218619
Net weight	0.466 kg