

KU-516

Order no.: 0160700

PRODUCT INFORMATION

Weatherproof horn driver

- Diecast version, IP66
- Protected against powerful water jets
- 3.5 cm (1⅜") mounting flange

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

KU-516	
Active/passive	passive
Transmission technology	cable

KU-516

Total power rating	75 W
Power rating (RMS)	50 W
Impedance	16 Ω
Frequency range	160-6,500 Hz
Number of speakers	1
SPL	113 dB/W/m
Radiation angle/beam angle	dep. on horn: SK-22, SK-159
Radiation angle, horizontal	dep. on horn
Radiation angle, vertical	dep. on horn
Housing material	diecast
Colour	dark grey
Mounting device	3.5 mm mounting flange
Protection class	IP66
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 126 mm x 100 mm
Width	Ø 126 mm
Height	Ø 126 mm
Depth	100 mm
Weight	1.9 kg
Inputs	screw terminal
Replacement voice coil	KU-516/VC
Other features	weatherproof
Packaging dimensions (W x H x L)	0.14 x 0.115 x 0.14 m
Gross weight	2.25 kg
Net weight	1.95 kg

KU-516

EAN code	4007754031249
Net weight	1.95 kg