

KU-616T

Order no.: 0160710

PRODUCT INFORMATION

Weatherproof horn driver

- 100 V transmission technology
- Protected against powerful water jets
- Power selector switch
- 3.5 cm (1⅜") mounting flange
- 55 cm connection cable

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

KU-616T

Active/passive	passive
Transmission technology	100 V
Total power rating	40 W
Power rating (RMS)	40/30/20/10/5 W
Frequency range	160-6,500 Hz
Number of speakers	1
SPL	112 dB/W/m
Radiation angle/beam angle	dep. on horn
Features	power selector switch
Housing material	metal
Colour	black
Mounting device	3.5 cm mounting flange
Protection class	IP66
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 150 mm x 136 mm
Width	Ø 150 mm
Height	Ø 150 mm
Depth	136 mm
Weight	2.2 kg
Inputs	cable connection
Replacement voice coil	KU-616T/VC
Other features	weatherproof
Packaging dimensions (W x H x L)	0.14 x 0.145 x 0.14 m
Gross weight	2.4 kg
Net weight	2.195 kg

KU-616T

EAN code	4007754031904
Net weight	2.195 kg