

KU-916T

Order no.: 0161610

PRODUCT INFORMATION

Weatherproof horn driver

- 100 V transmission technology
- Protected against powerful water jets
- Power selector switch
- 3.5 cm (1⅜") mounting flange
- 60 cm connection cable

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

KU-916T

Active/passive	passive
Transmission technology	100 V
Total power rating	60 W
Power rating (RMS)	60/50/40/30/20/10 W
Frequency range	160-7,000 Hz
Number of speakers	1
SPL	113 dB/W/m
Radiation angle/beam angle	dep. on horn
Features	power selector switch
Housing material	metal
Colour	dark grey
Mounting device	3.5 cm mounting flange
Protection class	IP66
Admiss. ambient temp.	-20 °C to +50 °C
Dimensions	Ø 150 mm x 158 mm
Width	Ø 150 mm
Height	Ø 150 mm
Depth	158 mm
Weight	2.75 kg
Inputs	cable connection
Replacement voice coil	KU-916T/VC
Other features	weatherproof
Packaging dimensions (W x H x L)	0.15 x 0.18 x 0.15 m
Gross weight	2.96 kg
Net weight	2.75 kg

KU-916T

EAN code	4007754171532
Net weight	2.75 kg