

PA-24AD

Order no.: 0171890

PRODUCT INFORMATION

10-way PA line splitter

- 2 separate inputs
- Stereo operation or mono operation
- Balanced XLR connection for each input and output
- Gain control for each output
- Peak indication for each input
- Mains operation and 24 V emergency power operation

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.
Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

PA-24AD

Description	splitter
Frequency range	20-20,000 Hz
Input signal	0.775 V
Input impedance	15 kΩ
Output signal	0.775 V
Output impedance	600 Ω
S/N ratio	> 68 dB
THD	< 0.05%
Admiss. ambient temp.	0-40 °C
Power supply	˜ 230 V/50 Hz/10 VA DC 24 V/0.2 A
Dimensions	482 x 45 x 235 mm, 1 RS
Weight	2.9 kg
Inputs	2 x XLR
Outputs	10 x XLR

PA-24AD

EAN code	4007754182255
Net weight	2.93 kg