

PA-26FMU

Order no.: 0175040

PRODUCT INFORMATION

PA emergency sound system,
for integrating into PA systems according to EN 60849.

- Hand-held microphone with operational monitoring
- Alarm input for triggering alarm
- Reproduction of MP3 voice recordings via integrated SD card slot (for media up to 32 GB, not supplied), volume control
- Siren emits an acoustic signal for 10 seconds when alarm is triggered, volume control
- Built-in signal light FIRE flashes when alarm is triggered
- Balanced line output via screw terminal contact
- 24 V power supply via PSS-3000SV, available at option

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety and warning notices

Only use the device indoors and protect it from dripping and splashing water, high humidity and heat (permissible operating temperature range 0 - 40 °C).
The heat generated in the device must be dissipated by air circulation. Therefore, do not cover the ventilation openings of the housing.
If the appliance is to be taken out of service permanently, hand it over to a local recycling centre for environmentally friendly disposal.

SPECIFICATIONS

PA-26FMU	
Output level	1.23 V/600 Ω, bal.
Siren frequency	800 Hz
Max. recording time	dep. on storage medium
Power supply	DC 24 V/200 mA
Dimensions	482 x 88 x 200 mm, 2 RS
Weight	3 kg

PA-26FMU	
EAN code	4007754253764
Net weight	3.63 kg