

PA-803DAP

Order no.: 1000168

PRODUCT INFORMATION

Mono class D PA mixing amplifier,
with integrated MP3 player, FM/DAB+ tuner and Bluetooth.

- 1 x 30 W
- Class D concept with high efficiency to cut energy costs
- Silent operation due to fanless cooling concept
- Bluetooth version 4.2
- MP3 player with USB/SD interface, FM/DAB+ radio, LED display, infrared remote control
- Reception of interference-free 'digital radio' (DAB+)
- 1 balanced XLR microphone input with 48 V phantom power and priority selection for announcements
- 2 unbalanced inputs, switchable mic/line
- 2 unbalanced line inputs
- 1 TEL input
- 1 Music-On-Hold output (MOH)
- Speaker outputs via screw contacts
- Mute function via screw contact
- 2 line outputs
- Input level control and output level control
- 2-way tone control for the output
- LEDs for indicating operation, clipping, protect and signal level

Manufacturer information:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages

The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.

During operation, there may be a hazard of contact with a dangerous voltage of up to 100 V at the speaker terminals. Always switch off the amplifier before making or changing any connections.

Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.

The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).

Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.

The heat generated inside the unit must be dissipated by air circulation; never cover the air vents of the housing.

If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

PA-803DAP	
Peak output power	30 W
Power rating	30 W
Power rating at 4 Ω	30 W
Power rating at 8 Ω	30 W
Power rating at 16 Ω	30 W
Power rating at 100 V	30 W
Power rating at 70 V	30 W
Channels	1
Zones	1
Inputs	4.5 mV/600 Ω (channel 1), 120 mV (channels 2-3), 60 mV (channels 4-5) 90 mV (tel.)
Frequency range	60-15,000 Hz
Equalizer bass	yes

PA-803DAP

Equalizer treble	yes
S/N ratio	72 dB (mic, channels 1-3) 85 dB (line, channels 2-5)
THD	< 0.5%
Phantom power	48 V
Power supply	˜ 230 V/50 Hz/100 VA DC 24 V/2.5 A
Mains voltage	~ 230 V
Mains frequency	50 Hz
Power consumption, operation	100 VA
Operating voltage (possible alternative)	DC 24 V
Power supply (possible alternative)	2.5 A
Admiss. ambient temp.	0-40 °C
Width	320 mm
Height	95 mm
Depth	245 mm
Weight	3.95 kg
Connections	1 x XLR (channel 1), 2 x 6.3 mm jack (channels 2-3), 2 x RCA L/R (channels 4-5), 2 x RCA (record out), 1 x F jack (FM/DAB+), screw contacts (tel. input), screw contacts (MOH), screw contacts (DC 24 V), screw contacts (mute), screw contact
Packaging dimensions (W x H x L)	0.39 x 0.16 x 0.31 m
Gross weight	4.33 kg
Net weight	3.74 kg

PA-803DAP

EAN code	4007754276015
Net weight	3.74 kg