

PDM-3

Order no.: 0234850

PRODUCT INFORMATION

Dynamic vocal microphone

- Frequency response especially optimised for the vocal spectrum
- Low handling noise and high acoustic feedback suppression
- Robust design for a long life
- Supplied with connection cable

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany

info@monacor.com

SPECIFICATIONS

PDM-3

Description	vocal microphone
Transmission method	cable
Polar pattern	cardioid
System	dynamic
Audio frequency range	50-16,500 Hz
Nominal impedance	600 Ω
Sensitivity	1.8 mV/Pa
Max. sound pressure	147 dB
Housing material	diecast metal
Admiss. ambient temp.	0-40 °C
Weight	315 g
Cable	XLR, bal.,XLR, bal.
Connection	XLR, bal.
Packaging dimensions (W x H x L)	0.12 x 0.08 x 0.255 m
Gross weight	0.755 kg
Net weight	0.6 kg

PDM-3

EAN code	4007754194258
Net weight	0.6 kg