

PDM-57

Order no.: 0234860

PRODUCT INFORMATION

Universal dynamic microphone

- For general sound pickup of instruments and for live performances
- Natural sound characteristics
- Characteristic sound with a high recognition value
- Supplied with connection cable

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany

info@monacor.com

SPECIFICATIONS

PDM-57

Description	universal microphone
Transmission method	cable
Polar pattern	cardioid
System	dynamic
Audio frequency range	50-16,500 Hz
Nominal impedance	600 Ω
Sensitivity	1.8 mV/Pa
Max. sound pressure	145 dB
Housing material	diecast metal
Admiss. ambient temp.	0-40 °C
Weight	250 g
Cable	XLR, bal.,XLR, bal.
Connection	XLR, bal.
Packaging dimensions (W x H x L)	0.12 x 0.08 x 0.255 m
Gross weight	0.715 kg
Net weight	0.56 kg

PDM-57

EAN code	4007754194265
Net weight	0.56 kg