

R-4TBM/5

Order no.: 0259841

PRODUCT INFORMATION

UHF PLL pocket transmitter

- Suitable for combination with a headband microphone or an instrument microphone with 4-pole mini XLR connector
- Bandwidth: 36 MHz
- 6 groups, each with up to 22 compatible preset channels
- 1,441 selectable individual frequencies
- REMOSET technology for receiver/transmitter synchronisation
- Adjustable sensitivity (±15 dB)
- Lock function
- 6-level display for indicating battery status and low battery alert, backlit LCD
- Switchable transmitting power

There are restrictions or requirements within the EU!

Please read the notes regarding wireless systems in the section “IMPORTANT INFORMATION”!

How many wireless systems can be operated simultaneously?
With optimum local conditions, it is possible to operate up to 18 wireless systems R-4/5,

R-4THA/5, JSS-4B/5, R-4TBM/5 simultaneously.

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries.
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.
Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

SPECIFICATIONS

R-4TBM/5

General information

Description	pocket transmitter
Carrier frequency range	506-542 MHz
Audio frequency range	50-18,000 Hz
Channels	1
Operating time	> 20 h
Admiss. ambient temp.	0-40 °C

Specifications transmitter

Transmitting power	10/50 mW
Operating range	120 m
Power supply transmitter	2 x batt. AA size (not supplied)

R-4TBM/5

Width transmitter	62 mm
Height transmitter	80 mm
Depth transmitter	23 mm
Weight transmitter	95 g
Connections transmitter	4-pole mini XLR

R-4TBM/5

EAN code	4007754268607
Net weight	0.115 kg