

RDA20

Order no.: 1001172

PRODUCT INFORMATION

Active speaker with integrated Dante® module

- Self-amplified speaker system, addressable via Dante® audio network
- Supports PoE/PoE+ Ethernet audio connection and power supply via RJ45 connection
- Output power: 10 W with PoE, 20 W with PoE+
- Supplied with 2 wall brackets
- Automatic assignment of an IP address via DHCP router
- Relacart speaker management software for easy setup and remote management

System requirements Dante®: Windows 7/8.1/10/11 or MacOS 10.9.5/10.10.5/10.11

The brand Dante® as well as the Dante® software which may have been integrated into these products are licenced by Audinate Pty Ltd

Please note: RELACART products are distributed by MONACOR INTERNATIONAL exclusively in the following countries: Germany, Austria, Switzerland, Netherlands, Belgium, Luxembourg, Denmark, Portugal, Malta. Orders from other countries cannot be fulfilled.

Manufacturer information:
Relacart Electronics Co., Ltd.
1408 Room, B Building
Fengxing Plaza
No. 242, Tianhe Road
Tianhe District
Guangzhou, Guangdong
China
info@relacart.com

Importer:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Never adjust the speakers to a very high volume. Permanent high volumes may damage your hearing!
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.

SPECIFICATIONS

RDA20	
Active/passive	active
Transmission technology	Dante®
Total output power	30 W
Power rating (RMS)	10 W (PoE), 20 W (PoE+)
Frequency range	85-17,000 Hz
System	2-way
Bass speaker	10 cm (4") cone speaker
Tweeter	7.6 cm (3") cone tweeter
Number of speakers	2
Speaker size	10 cm (4")
SPL	96 dB/W/m
Max. rated SPL	110 dB

RDA20

Radiation angle/beam angle	90°
Radiation angle, horizontal	90°
Radiation angle, vertical	90°
Housing material	wood, protective metal grille
Colour	white
Mounting device	wall bracket
Power supply	37-57 V PoE/PoE+ via RJ45
Dimensions	132 x 235 x 142 mm
Width	132 mm
Height	235 mm
Depth	142 mm
Weight	2.36 kg
Inputs	1 x RJ45 (Dante® IN)
Other features	integr. DSP for tone control via software
Packaging dimensions (W x H x L)	0.205 x 0.33 x 0.215 m
Gross weight	2.95 kg
Net weight	2.36 kg

RDA20

EAN code	4007754426700
Net weight	2.36 kg