

SL-60SW/EN

Order no.: 1001524

PRODUCT INFORMATION

Weatherproof PA speaker system with a 13 cm (5.25") coaxial horn loudspeaker, designed for outdoor applications and offering excellent music reproduction. The SL-60SW/EN is ideally suited for use in a wide range of venues, including hotels, shopping centres, and amusement parks.

Weatherproof 60 W PA speaker system
with EN 54-24 certification

- 100 V line operation or 8 Ω operation
- 2-way bass-reflex system
- 13 cm (5.25") coaxial loudspeaker with high-frequency driver and crossover network
- Excellent sound quality
- Tested in accordance with IP66
- ABS enclosure with metal protective grille
- Recessed connection terminal with cover plate and PG cable gland
- Safety cable included
- Mounting bracket made of corrosion-resistant stainless steel

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG

Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

SL-60SW/EN	
Active/passive	passive
Transmission technology	100 V or low-impedance
Total power rating	60 W
Power rating (RMS)	60/30/15 W
Impedance	8 Ω
Frequency range	100-24,000 Hz
System	2-way coaxial
Bass speaker	13 cm (5.25")
Tweeter	tweeter
Number of speakers	2
Speaker size	13 cm (5.25")
SPL	89 dB/W/m
Max. rated SPL	95.6 dB
Radiation angle/beam angle	360°/360° (500 Hz) 140°/154° (1 kHz) 87°/87° (2 kHz) 103°/94° (4 kHz)
Radiation angle, horizontal	360° (500 Hz) 140° (1 kHz) 87° (2 kHz) 103° (4 kHz)
Radiation angle, vertical	360° (500 Hz) 154° (1 kHz) 87° (2 kHz) 94° (4 kHz)
Housing material	ABS
Colour	black (RAL 9005)
Mounting device	mounting bracket
Protection class	IP66
Admiss. ambient temp.	-25 °C to +70 °C
Dimensions	180 x 180 x 194 mm
Width	180 mm
Height	180 mm
Depth	194 mm
Weight	2.7 kg
Inputs	screw terminal

SL-60SW/EN

Packaging dimensions (W x H x L)	0.18 × 0.18 × 0.194 m
Net weight	2.7 kg

SL-60SW/EN

EAN code	4007754430530
Net weight	2.7 kg