


SP-15

Order no.: 0100310

PRODUCT INFORMATION

Special speaker, 10 W, 8 Ω

- All-plastic cone with hard suspension
- Moisture-proof
- Special version for signal sounds of alarm systems
- Operating temperature range: -25 °C to +70 °C

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

SP-15	
Impedance (Z)	8 Ω

SP-15

Transmission technology	cable
Frequency range	f3-8,000 Hz
Resonant frequency (fs)	430 Hz
Power rating (RMS)	10 W
Peak music power output (MAX)	15 W
SPL	96 dB/W/m
Magnet weight	150 g
Magnet diameter	Ø 60 mm
Mounting cutout	Ø 79 mm
Mounting depth	39 mm
Dimensions	85 x 85 x 39 mm
Width	85 mm
Height	85 mm
Depth	39 mm
Colour	transparent
Admiss. ambient temp.	-25 °C to +70 °C
Weight	0.355 kg
Packing unit	1
Type of speaker	3"
Packaging dimensions (W x H x L)	0.09 x 0.05 x 0.09 m
Gross weight	0.38 kg
Net weight	0.355 kg

SP-15

EAN code	4007754024289
Net weight	0.355 kg