

SP-60/4

Order no.: 0100730

PRODUCT INFORMATION

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

SP-60/4	
Impedance (Z)	4 Ω
Transmission technology	cable
Frequency range	f3-8,000 Hz
Resonant frequency (fs)	65 Hz
Power rating (RMS)	30 W
Peak music power output (MAX)	60 W
SPL	90 dB/W/m

SP-60/4

Suspension compl. (Cms)	0.8 mm/N
Moving mass (Mms)	4 g
Mech. Q factor (Qms)	2,10
Electr. Q factor (Qes)	0,64
Total Q factor (Qts)	0,49
Equivalent volume (Vas)	6 l
DC resistance (Re)	3.3 Ω
Force factor (BxL)	2.9 Tm
Voice coil induct. (Le)	0.2 mH
Voice coil diameter	Ø 25.5 mm
Voice coil former	aluminium
Linear excursion (XMAX)	± 2 mm
Eff. cone area (Sd)	55 cm^2
Magnet weight	280 g
Magnet diameter	Ø 80 mm
Mounting cutout	Ø 96 mm
Mounting depth	60 mm
Dimensions	105 x 105 x 60 mm
Width	105 mm
Height	105 mm
Depth	60 mm
Colour	black
Admiss. ambient temp.	0-40 °C
Weight	0.654 kg
Packing unit	1
Type of speaker	4"
Packaging dimensions (W x H x L)	0.11 x 0.065 x 0.115 m
Gross weight	0.685 kg
Net weight	0.654 kg

SP-60/4

EAN code	4007754024807
Net weight	0.654 kg