

SPE-8U

Order no.: 0105640

PRODUCT INFORMATION

Hi-fi wall and ceiling speaker for flush mounting, 8 Ω

- High-quality 2-way coaxial speaker system with excellent sound characteristics
- 20 cm (8") bass speaker with glass fibre cone, 24 mm (1") dome tweeter with titanium cone
- Plastic tray for flush mounting in walls or solid ceilings
- Required hole in wall: approx. 242 x 242 x 100 mm
- Metal front grille with plastic frame

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

SPE-8U	
Impedance (Z)	8 Ω

SPE-8U

Transmission technology	cable
Frequency range	70-20,000 Hz
Resonant frequency (fs)	60 Hz
Power rating (RMS)	30 W
Peak music power output (MAX)	60 W
SPL	89 dB/W/m
Mounting cutout	242 x 242 mm
Mounting depth	100 mm
Dimensions	248 x 248 x 100 mm
Width	248 mm
Height	248 mm
Depth	100 mm
Colour	white
Admiss. ambient temp.	0-40 °C
Weight	1.6 kg
Packing unit	1
Type of speaker	200
Packaging dimensions (W x H x L)	0.265 x 0.12 x 0.265 m
Gross weight	1.78 kg
Net weight	1.62 kg

SPE-8U

EAN code	4007754232721
Net weight	1.62 kg