

SPH-30X/8SW

Order no.: 0104190

PRODUCT INFORMATION

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

SPH-30X/8SW	
Impedance (Z)	8 Ω
Transmission technology	cable
Frequency range	f3-17,000 Hz
Resonant frequency (fs)	105 Hz
Power rating (RMS)	20 W
Peak music power output (MAX)	50 W
SPL	87 dB/W/m

SPH-30X/8SW

Suspension compl. (Cms)	0.90 mm/N
Moving mass (Mms)	2.65 g
Mech. Q factor (Qms)	8,59
Electr. Q factor (Qes)	0,49
Total Q factor (Qts)	0,42
Equivalent volume (Vas)	1.3 l
DC resistance (Re)	5.7 Ω
Force factor (BxL)	4.48 Tm
Voice coil induct. (Le)	0.5 mH
Voice coil diameter	Ø 21 mm
Voice coil former	Kapton
Linear excursion (XMAX)	± 2 mm
Eff. cone area (Sd)	30 cm^2
Magnet weight	neodymium
Mounting cutout	Ø 73 mm
Mounting depth	40.7 mm
Dimensions	Ø 80.5 mm x 42 mm
Width	80.5 mm
Height	80.5 mm
Depth	42 mm
Colour	black
Admiss. ambient temp.	0-40 °C
Weight	141 g
Packing unit	1
Type of speaker	3"
Packaging dimensions (W x H x L)	0.085 x 0.06 x 0.085 m
Gross weight	0.177 kg
Net weight	0.141 kg

SPH-30X/8SW

EAN code	4007754230826
Net weight	0.141 kg