

SPM-205/4

Order no.: 0105380

PRODUCT INFORMATION

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

SPM-205/4	
Impedance (Z)	4 Ω
Transmission technology	cable
Frequency range	f3-5,000 Hz
Resonant frequency (fs)	37 Hz
Power rating (RMS)	70 W
Peak music power output (MAX)	150 W
SPL	89 dB/W/m

SPM-205/4

Suspension compl. (Cms)	0.98 mm/N
Moving mass (Mms)	18 g
Mech. Q factor (Qms)	2,71
Electr. Q factor (Qes)	0,68
Total Q factor (Qts)	0,55
Equivalent volume (Vas)	72 l
DC resistance (Re)	3.6 Ω
Force factor (BxL)	4.75 Tm
Voice coil induct. (Le)	0.65 mH
Voice coil diameter	Ø 25.5 mm
Voice coil former	aluminium
Linear excursion (XMAX)	± 3 mm
Eff. cone area (Sd)	210 cm^2
Magnet weight	380 g
Magnet diameter	Ø 80 mm
Mounting cutout	Ø 183 mm
Mounting depth	80 mm
Mounting hole diameter	Ø 216 mm
Dimensions	Ø 200 mm x 88 mm
Outside diameter	Ø 200 mm
Width	Ø 200 mm
Height	Ø 200 mm
Depth	88 mm
Colour	black
Admiss. ambient temp.	0-40 °C
Weight	1.062 kg
Packing unit	1
Type of speaker	8"
Packaging dimensions (W x H x L)	0.215 x 0.125 x 0.215 m
Gross weight	1.23 kg
Net weight	1.062 kg

SPM-205/4

EAN code	4007754220995
Net weight	1.062 kg