

SPM-205/8

Order no.: 0105390

PRODUCT INFORMATION

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

SPM-205/8	
Impedance (Z)	8 Ω
Transmission technology	cable
Frequency range	f3-5,000 Hz
Resonant frequency (fs)	37 Hz
Power rating (RMS)	70 W
Peak music power output (MAX)	150 W
SPL	89 dB/W/m

SPM-205/8

Suspension compl. (Cms)	0.75 mm/N
Moving mass (Mms)	22 g
Mech. Q factor (Qms)	2,95
Electr. Q factor (Qes)	0,92
Total Q factor (Qts)	0,7
Equivalent volume (Vas)	54 l
DC resistance (Re)	7.2 Ω
Force factor (BxL)	6.5 Tm
Voice coil induct. (Le)	0.7 mH
Voice coil diameter	Ø 25.5 mm
Voice coil former	aluminium
Linear excursion (XMAX)	± 3 mm
Eff. cone area (Sd)	210 cm^2
Magnet weight	380 g
Magnet diameter	Ø 80 mm
Mounting cutout	Ø 183 mm
Mounting depth	80 mm
Mounting hole diameter	Ø 216 mm
Dimensions	Ø 200 mm x 88 mm
Outside diameter	Ø 200 mm
Width	Ø 200 mm
Height	Ø 200 mm
Depth	88 mm
Colour	black
Admiss. ambient temp.	0-40 °C
Weight	1.4 kg
Packing unit	1
Type of speaker	8"
Packaging dimensions (W x H x L)	0.215 x 0.125 x 0.215 m
Gross weight	1.5 kg
Net weight	1.4 kg

SPM-205/8

EAN code	4007754221008
Net weight	1.4 kg