

ST-850

Order no.: 0235510

PRODUCT INFORMATION

Gooseneck microphone for an optional wireless operation

- Matching pocket transmitters of the PT series
- High-quality back electret cartridge with supercardioid polar pattern
- Low-noise reed switch for on/off
- LED status indicator
- Solid diecast housing
- Optional pocket transmitter can be attached to the diecast base

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68

28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

ST-850

Description	gooseneck microphone
Version	desktop, wireless
Transmission method	cable/wireless
Polar pattern	supercardioid
System	back electret
Audio frequency range	50-18,000 Hz
Nominal impedance	2 kΩ/100 Ω
Sensitivity	5 mV/Pa, 15.8 mV/Pa
Max. sound pressure	125 dB
Power supply	via pocket transmitter, +48 V phantom power
Gooseneck length	305 mm
Admiss. ambient temp.	0-40 °C
Dimensions	110 x 65 x 150 mm
Weight	693 g
Connection	4-pole mini XLR inline jack, XLR panel plug
Packaging dimensions (W x H x L)	0.13 x 0.45 x 0.195 m
Gross weight	1.271 kg
Net weight	0.693 kg

ST-850

EAN code	4007754202304
Net weight	0.693 kg