

TK-350

Order no.: 0234880

PRODUCT INFORMATION

Dynamic vocal microphone

- Frequency response optimised for vocals
- Clear voice reproduction
- Powerful band sound
- Minimised handling noise and structure-borne noise, low susceptibility to acoustic feedback
- High-quality reed switch allows silent switching actions
- Supplied with connection cable

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68

28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

TK-350

Description	vocal microphone
Transmission method	cable
Polar pattern	cardioid
System	dynamic
Audio frequency range	80-12,000 Hz
Nominal impedance	600 Ω
Sensitivity	1.8 mV/Pa
Max. sound pressure	145 dB
Housing material	diecast metal
Admiss. ambient temp.	0-40 °C
Weight	380 g
Cable	XLR, bal.,XLR, bal.
Connection	XLR, bal.
Packaging dimensions (W x H x L)	0.13 x 0.075 x 0.26 m
Gross weight	0.783 kg
Net weight	0.626 kg

TK-350

EAN code	4007754194296
Net weight	0.626 kg