

TM-929

Order no.: 0234940

PRODUCT INFORMATION

Dynamic vocal microphone

- High-quality entry-level microphone, classic design
- Robust body
- Suppression of handling noise and acoustic feedback
- Low-noise reed switch
- Supplied with connection cable

tools4music 06/2011
“Proved to be an acoustic surprise, showed an amazingly well-balanced radiation.”

Manufacturer information:
JTS PROFESSIONAL CO., LTD.
No. 148, Gongye 9th Rd., Dali Dist.
41280 Taichung City
Taiwan
jts@jts.com.tw

EU-Representative:

MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

SPECIFICATIONS

TM-929

Description	vocal microphone
Transmission method	cable
Polar pattern	cardioid
System	dynamic
Audio frequency range	50-15,000 Hz
Nominal impedance	600 Ω
Sensitivity	1.8 mV/Pa
Max. sound pressure	148 dB
Housing material	diecast metal
Admiss. ambient temp.	0-40 °C
Weight	350 g
Cable	XLR, bal., 6.3 mm plug, unbal.
Connection	XLR, bal.
Packaging dimensions (W x H x L)	0.12 x 0.08 x 0.255 m
Gross weight	0.725 kg
Net weight	0.556 kg

TM-929

EAN code	4007754194357
Net weight	0.556 kg