

# TS-C20-500/T

Order no.: 0163730

## PRODUCT INFORMATION

**Weatherproof PA column speaker,**
with EN 54-24 certification.

- 100 V transmission technology
- 4 x 7.7 cm (3") waterproof full range speaker
- 4 power taps: 20/15/10/5 W
- Connection via ceramic terminals with thermal fuse in the cabinet
- 2 x PG9 cable gland
- Robust, plastic-coated aluminium cabinet with front protective grille
- The speaker complies with British Standard BS 5839, part 8
- Supplied with plastic wall bracket for pivoting and tilting

**Manufacturer information**
ic audio GmbH
Boehringerstr. 14a
68307 Mannheim
Germany
info@ic-audio.com

# SPECIFICATIONS

**TS-C20-500/T**

| | |
|---|---|
| Active/passive | passive |
| Transmission technology | 100 V |
| Total power rating | 20 W |
| Power rating (RMS) | 20/15/10/5 W |
| Frequency range | 200-17,000 Hz |
| Full range speaker | 4 x 77 mm |
| Number of speakers | 4 |
| Speaker size | 7.5 cm (3") |
| SPL | 97 dB/W/m |
| Max. rated SPL | 109 dB |
| Radiation angle/beam angle | H: 149°/V: 38° |
| Radiation angle, horizontal | 149° |
| Radiation angle, vertical | 38° |
| Housing material | aluminium |
| Colour | white aluminium, RAL 9006 |
| Mounting device | wall bracket |
| Protection class | IP66 |
| Admiss. ambient temp. | -20 °C to +90 °C |
| Dimensions | 100 x 510 x 92 mm |
| Width | 100 mm |
| Height | 510 mm |
| Depth | 92 mm |
| Weight | 2.8 kg |
| Inputs | ceramic screw terminals |
| Packaging dimensions (W x H x L) | 0.18 x 0.2 x 0.6 m |
| Gross weight | 3.3 kg |
| Net weight | 2.83 kg |

**TS-C20-500/T**

| | |
|---|---|
| EAN code | 4260590180490 |
| Net weight | 2.83 kg |