TXS-2402SET

Order no.: 0254090

PRODUCT INFORMATION

With the TXS-2402SET,
the entry into the world of digital wireless transmission will become a special sound experience. The signal transmission in the 2.4 GHz range is particularly stable and impresses by a high resistance to interference. The system manages without a compander which results in an incredibly dynamic efficiency and a voice transmission with a unique sound quality. Two systems can be used in parallel operation. Thus 4 microphone transmission paths can be used simultaneously. Licence-free system. The particularly easy and convenient use of the units and appealing design make the TXS-2402SET a real digital experience for the user.

Digital wireless 2-channel PLL microphone system, 2.4 GHz

- 2 microphone transmitters, 1 receiver, 1 plug-in power supply
- High resistance to interference due to digital transmission
- 2 systems can be used in parallel (corresponds to 4 microphone transmission paths)
- 16 frequencies (2,404-2,476 MHz) for each channel can be selected at the transmitter
- Wireless auto-configuration of the receiver
- Volume control for each channel
- 6.3 mm output for mixed signal
- Microphone cartridges with supercardiod polar pattern

Licence-free in the EU.

tastenwelt 06/2012
“An entry-level wireless system with a perfectly functioning technology.”
+ Easy operation
+ Well-balanced hand-held transmitter

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68

28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.
Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.
Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries/rechargeable batteries.
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal which is not harmful to the environment.
Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

SPECIFICATIONS

TXS-2402SET

General information

Description	wireless microphone system
Carrier frequency range	2,404-2,476 MHz
Audio frequency range	80-12,000 Hz
Channels	2
THD	< 0.1%
Dynamic range	87 dB
Admiss. ambient temp.	0-40 °C

Specifications transmitter

Transmitting power	10 mW
Operating range	approx. 30 m (free field) approx. 20 m (indoors)
Power supply transmitter	2 x 1.5 V batt. AA size
Width transmitter	54 mm
Height transmitter	54 mm
Depth transmitter	225 mm

TXS-2402SET

Weight transmitter	120 g

Specifications receiver

Audio signal receiver	100 mV/600 Ω
Power supply receiver	via encl. plug-in power supply
Width receiver	220 mm
Height receiver	45 mm
Depth receiver	150 mm
Weight receiver	550 g
Connections receiver	1 x 6.3 mm jack, unbal.

TXS-2402SET

EAN code	4007754226836
Net weight	1.066 kg