TXS-812SET

Order no.: 0252600

PRODUCT INFORMATION

Wireless 2-channel microphone system

- 2 microphone transmitters, 1 receiver, 1 plug-in power supply
- Two-channel UHF version (non-diversity) with channel mixing function which can additionally be selected
- Volume and squelch controls for each channel
- Each channel with LEDs for indicating RF signal and audio signal

Licence-free in the EU.

Manufacturer information:
MONACOR INTERNATIONAL GmbH & Co. KG
Konsul-Smidt-Str. 68
28217 Bremen
Germany
info@monacor.com

Safety Notes and Warning Messages
The unit uses dangerous mains voltage. Leave servicing to skilled personnel only and do not insert anything into the air vents. Inexpert handling may result in electric shock.
Do not operate the unit and disconnect the mains plug from the socket immediately if the unit or the mains cable is visibly damaged; if a defect might have occurred after the unit was dropped or suffered a similar accident, if malfunctions occur. In any case, the unit must be repaired by skilled personnel.
The unit is suitable for indoor use only. Protect it against dripping water and splash water, high air humidity and heat (admissible ambient temperature range: 0 - 40 °C).
Never pull the mains cable to disconnect the mains plug from the socket, always seize the plug.
Remove the rechargeable batteries or batteries if the device is not in use for a longer period of time (e.g. more than a week). This avoids possible damage through leaking batteries/rechargeable batteries.
If the unit is to be put out of operation permanently, take it to a local recycling plant for a disposal

which is not harmful to the environment.
Batteries and rechargeable batteries must not be disposed of with household waste. They must be disposed of in accordance with local regulations for hazardous waste.

SPECIFICATIONS

TXS-812SET

General information

Description	wireless microphone system
Carrier frequency range	863.80 MHz , 864.20 MHz
Audio frequency range	40-15,000 Hz
Channels	2
THD	< 0.5%
Dynamic range	> 90 dB
RF S/N ratio	> 80 dB
Admiss. ambient temp.	0-40 °C

Specifications transmitter

Transmitting power	< 10 mW
Operating range	approx. 30 m
Power supply transmitter	2 x 1.5 V batt. AA size (not supplied)
Width transmitter	52 mm
Height transmitter	52 mm
Depth transmitter	260 mm
Weight transmitter	240 g

Specifications receiver

Audio signal receiver	0-200 mV/10 kΩ (jack)0-400 mV/10 kΩ (XLR, bal.)
Power supply receiver	via encl. plug-in power supply
Width receiver	210 mm
Height receiver	46 mm
Depth receiver	190 mm
Weight receiver	560 g
Connections receiver	2 x XLR, bal.1 x 6.3 mm jack, unbal.

TXS-812SET

EAN code	4007754215175
Net weight	1.355 kg